




Performance



Technical Information



Features

Type:

Pistonc Diaphragmatic Absorber
 Absorption Range: 80 Hz to 120 Hz
 Peak Absorption Frequency: 90 Hz

Material:

- Natural Wood veneer
- Marine-grade plywood structural frame
- Calibrated cell acoustic foam

This panels can only be installed on vertical wall corners. Not for ceiling use.

Dimensions:

FG - NW | 595x1190x143mm | 13.0 Kg

With a peak absorption from 80 Hz to 120 Hz, the Wall Bass Trap offers an enriched acoustic experience, directly attenuating standing waves. The various front designs available for the Wall Bass Trap allow you to create artistic patterns when mounted on the walls of your home cinema or living room, completely indistinguishable from the Artnovion absorber range.

The Wall Bass Trap - 595 x 1190 - equivalent to 2 standard panels, is equipped with a weighted piston membrane enclosing a volume with a high performance acoustic core. This design allows for a precisely tuned, high performance absorption. Bringing you the maximum performance in as least space as possible.

Product finishes

(FG - NW) Natural Wood Finishes




FG | (W03) Wenge



FG | (W04) Fagus

Eiger W - Bass Trap - Wall

Wall Bass Trap



Purpose

- Room mode control
- Bass ratio control
- Low frequency RT reduction
- Improving low frequency response
- Reducing low frequency time decay

Recommended for

- Vertical Wall
- Small Room Acoustics
- Acoustic pressure zones

Fixing Systems

Add-ons



+ [FixArt Connect](#)

Wall



+ [FixArt - Tube](#)